





About Mustang Dynamometer

Known As The Best By The Best!

For over 50 years, Mustang Dynamometers has been a leading manufacturer and designer of the highest quality, most accurate chassis dynamometers for the performance market and emission

"The accurate loading and repeatability of our Mustang
Dyno gives us the confidence to know that vehicles will perform on the race track or street exactly as they do on the dyno."

- CobbTuning.com

testing programs worldwide. Mustang dynos are better because they help make our customers more successful. Mustang has perfected the art and science of vehicle loading and dynamometer control and has a complete lineup of performance tuning products. For the best tuning results, you need a dyno that applies an accurate load, like the car would see on the road or track. Some other dynos might give higher horsepower readings to try to impress, but if those readings are not based on actual realworld loading, and chances are that horsepower won't be there when you

need it at the track. Mustang Dynamometer is the most accurate and reliable dyno because it provides real-world loading and precise control. That's why Mustang is known as the best by the best

Philosophy

Mustang Dynamometer has always focused on our guiding principles: build the best equipment, deliver the best service and help our customers become the best in their field.

Flexibility

From engine dynamometers, transmission dynamometers, chassis dynamometers, from heavy equipment manufacturers to arenas such as NASCAR and the Indy Racing League, Mustang delivers accurate, high-performance testing and tuning abilities that professionals demand. Also we have developed custom applications for clients such as NASA, Caterpillar, Harley-Davidson, and The U.S. Military.

Quality

Mustang Dynamometer is the only dyno manufacturer in the industry to attain ISO 9001:2015 quality certification. All of Mustang's research and development, software design, manufacturing, electrical, and fabrication operations are done inhouse to ensure that the dynamometers we produce are state-of-the-art and deliver on our promise to be the best dynamometers in the industry.



Chassis Dynamometers At a Glance

| 2WD Model | Upgradeable to AWD | Max. HP | Inertia | Max. Speed | Roll Dia. | Maximum Axle Weight |
|----------------------|-----------------------|------------|------------|------------|-----------|------------------------|
| MD-100-SE | - | 900 HP | 2,000 lbs. | 165 mph | 8.575" | 6,000 lbs. |
| MD-150-SE | - | 1,200 HP | 630 lbs. | 175 mph | 8.575" | 6,000 lbs. |
| MD-250-SE | - | 1,500 HP | 2,000 lbs. | 175 mph | 10.7" | 12,000 lbs. |
| MD-500-SE-XL | YES | 1,500 HP | 2,000 lbs. | 190 mph | 12.625" | 6,000 lbs.* |
| MD-500-SE 80-inch OT | YES | 1,500 HP | 1,190 lbs. | 190 mph | 12.625" | 6,000 lbs.* |
| MD-600-SE | - | 2,000 HP | 2,000 lbs. | 200 mph | 19.75" | 6,000 lbs. |
| MD-800-SE | YES | 2,000 HP | 1,555 lbs. | 200 mph | 24" | 10,000 lbs. |
| MD-1000-SE | YES** | 2,000 HP | 3,000 lbs. | 125 mph | 17.7" | 24,000 lbs. |
| MD-1100 | YES | 2,500 HP | 1,500 lbs. | 200 mph | 30" | 10,000 lbs. |
| MD-1750-SE | YES | 3,000 HP | 2,530 lbs. | 250 mph | 50" | 10,000 lbs. |



| AWD Model | Max. HP AWD/2WD | Inertia AWD/2WD | Max. Speed AWD/2WD | Roll Dia. | Maximum Axle Weight |
|-------------------|--------------------|--------------------|-----------------------|---------------|------------------------|
| MD-AWD-150-SE-V8 | 2,000 / 1,200 HP | 1,260 / 630 lbs. | 155 / 165 mph | 8.575" | 6,000 lbs. |
| MD-AWD-500-SE-XL | 3,000 / 1,500 HP | 3,625 / 2,000 lbs. | 175 / 190 mph | 12.625" | 6,000 lbs. |
| MD-AWD-800-DE 24X | 3,000 / 2,000 HP | 1,800 / 900 lbs. | 175 / 200 mph | 24" | 10,000 lbs. |
| MD-AWD-1100-SE | 3,500 / 2,500 HP | 3,300 / 1,500 lbs. | 175 / 225 mph | 30" & 12.625" | 10,000 lbs. |
| MD-AWD-1750-SE | 3,500 / 3,000 HP | 3,300 / 2,530 lbs. | 150 / 250 mph | 50" & 12.625" | 10,000 lbs. |

3

NOTES: * 12,000 lbs. Available

** Only if ordered with special frame



2 Wheel Drive Dynamometers

MD-100-5E

| Max Horsepower | 90HP | |
|-----------------|--|---------|
| Max Speed | 165MPH | 266KPH |
| Roll Diameter | 8.575" | 21.8cm |
| Face Length | 35" | 89.0cm |
| Inner Track | 30" | 76.0cm |
| Outer Track | 100" | 254.0cm |
| Space Between | 17.1" | 43.4cm |
| Inertia | 2,000 lbs | 907kg |
| Max Axle Weight | 6,000 lbs | 2,722kg |
| Power Req.: | 115VAC, 1 phase, 15A 230VAC, 1 phase, 40A | |
| | | |

MD-150-SE

| Max Horsepower 1,200HP Max Speed 175MPH 282KPH Roll Diameter 8.575" 21.8cm Face Length 35" 89.0cm Inner Track 18" 45.7cm Outer Track 88" 223.5cm Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A 230VAC, 1 phase, 40A | | | |
|---|-----------------|-----------|---------|
| Roll Diameter 8.575" 21.8cm Face Length 35" 89.0cm Inner Track 18" 45.7cm Outer Track 88" 223.5cm Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Max Horsepower | 1,200HP | |
| Face Length 35" 89.0cm Inner Track 18" 45.7cm Outer Track 88" 223.5cm Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Max Speed | 175MPH | 282KPH |
| Inner Track 18" 45.7cm Outer Track 88" 223.5cm Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Roll Diameter | 8.575" | 21.8cm |
| Outer Track 88" 223.5cm Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Face Length | 35" | 89.0cm |
| Space Between 17.1" 43.4cm Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Inner Track | 18" | 45.7cm |
| Inertia 630 lbs 286kg Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Outer Track | 88" | 223.5cm |
| Max Axle Weight 6,000 lbs 2,722kg Power Req.: 115VAC, 1 phase, 15A | Space Between | 17.1" | 43.4cm |
| Power Req.: 115VAC, 1 phase, 15A | Inertia | 630 lbs | 286kg |
| | Max Axle Weight | 6,000 lbs | 2,722kg |
| | Power Req.: | , | ' |

MD-250-SE

| ב טנש טואו | | |
|-----------------|----------------------------|---------|
| Max Horsepower | 1,500HP | |
| Max Speed | 175MPH | 282KPH |
| Roll Diameter | 10.7" | 27.2cm |
| Face Length | 40" | 101.6cm |
| Inner Track | 28" | 71.1cm |
| Outer Track | 108" | 274.3cm |
| Roll Spacing | 19.6" | 49.8cm |
| Inertia | 2,000 lbs | 907kg |
| Max Axle Weight | 12,000 lbs | 5,443kg |
| Power Req.: | 115VAC, 1 p 230VAC, 1 p | , |

Air Requirement for All 2WD Dynamometers: 100 PSI, dry, regulated, oil-free.

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual

Road Simulation Technology.



MustangDyne.com **5** (330) 963-5400



2 Wheel Drive Dynamometers





| Max Horsepower | 1,500HP | |
|-----------------|--|---------|
| Max Speed | 190MPH | 306KPH |
| Roll Diameter | 12.625" | 32.1cm |
| Face Length | 31" | 78.7cm |
| Inner Track | 18" | 45.7cm |
| Outer Track | 80" | 203.2cm |
| Inertia | 1,190 lbs | 540kg |
| Max Axle Weight | 6,000 lbs | 2,722kg |
| Power Req.: | 115VAC, 1 phase, 15A 230VAC, 1 phase, 40A | |
| | | |

MD-500-5E XL

| Max Horsepower | 1,500HP | |
|-----------------|-----------|--------------------------|
| Max Speed | 190MPH | 306KPH |
| Roll Diameter | 12.625" | 32.1cm |
| Face Length | 37" | 93.9cm |
| Inner Track | 24" | 60.9cm |
| Outer Track | 98" | 248.9cm |
| Inertia | 2,000 lbs | 907kg |
| Max Axle Weight | 6,000 lbs | 2,722kg |
| Power Req.: | | phase, 15A phase, 40A |
| | | |

MD-600 Series

| WD 000 3E | .,,,,, | |
|-----------------|----------------------------|---------|
| Max Horsepower | 1,500HP | |
| Max Speed | 175MPH | 282KPH |
| Roll Diameter | 19.75" | 50.2cm |
| Face Length | 41" | 104.1cm |
| Inner Track | 24" | 66.1cm |
| Outer Track | 108" | 274.3cm |
| Inertia | 2,000 lbs | 907kg |
| Max Axle Weight | 6,000 lbs | 2,722kg |
| Power Req.: | 115VAC, 1 բ 230VAC, 1 բ | |

Air Requirement for All 2WD Dynamometers: 100 PSI, dry, regulated, oil-free.

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual

Road Simulation Technology.



2 Wheel Drive Dynamometers



| Max Horsepower | 2,000HP | |
|-----------------|------------------------------|---------|
| Max Speed | 200MPH | 322KPH |
| Roll Diameter | 24" | 60.9cm |
| Face Length | 28.5" | 72.4cm |
| Inner Track | 29" | 73.7cm |
| Outer Track | 86" | 218.4cm |
| Inertia | 900 lbs | 408kg |
| Max Axle Weight | 10,000 lbs | 4,536Kg |
| Power Req.: | 115VAC, 1 pt 230VAC, 1 pt | , |
| | | |

MD-1100 Series

| Max Horsepower | 2,500HP | |
|-----------------|----------------------------|----------|
| Max Speed | 200MPH | 322KPH |
| Roll Diameter | 30" | 76.2cm |
| Face Length | 50"&28" | 127&71cm |
| Inner Track | 30" | 76.2cm |
| Outer Track | 108" | 274.3cm |
| Inertia | 2,000 lbs | 907kg |
| Max Axle Weight | 10,000 lbs | 4,536Kg |
| Power Req.: | 115VAC, 1 բ 230VAC, 1 բ | , |
| | | |

MN-1750 Series

| ב טביו טואו | JEI IES | |
|-----------------|----------------------------|---------|
| Max Horsepower | 3,000HP | |
| Max Speed | 250MPH | 402KPH |
| Roll Diameter | 50" | 127.0cm |
| Face Length | 28" | 71.1cm |
| Inner Track | 28" | 71.1cm |
| Outer Track | 84" | 213.4cm |
| Inertia | 2,530 lbs | 1,148kg |
| Max Axle Weight | 10,000 lbs | 4,536Kg |
| Power Req.: | 115VAC, 1 p 230VAC, 1 p | |

Air Requirement for All 2WD Dynamometers: 100 PSI, dry, regulated, oil-free.

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual


Road Simulation Technology.



All Wheel Drive Dynamometers



| Max Horsepower | 2,000HP(AWD) 1,200HP(2WD) | |
|--------------------------------|--------------------------------|-----------|
| Max Speed | 165MPH | 266KPH |
| Roll Diameter | 8.575" | 21.8cm |
| Face Length | 35" | 89.0cm |
| Inner Track | 30" | 76.0cm |
| Outer Track | 86" | 218.4cm |
| Wheelbase Range | 96-122" | 244-310cm |
| Inertia | 1,260 lbs(A 630 lbs(2W | , |
| Max Axle Weight | 6,000 lbs | 2,722Kg |
| Power Req.: 230VAC, 230VAC, | 1 phase, 60 H 3 phase, 60 H | |



MD-AWD-500 Series

| Max Horsepower | 3,000HP(AWD) 1,500HP(2WD) | |
|--------------------------------|----------------------------------|-----------|
| Max Speed | 190MPH | 306KPH |
| Roll Diameter | 12.625" | 32.1cm |
| Face Length | 31" | 78.7cm |
| Inner Track | 18" | 45.7cm |
| Outer Track | 80" | 203.2cm |
| Wheelbase Range | 88-118" | 224-300cm |
| Inertia | 2,152 lbs(AWD) 1,190 lbs(2WD) | |
| Max Axle Weight | 6,000 lbs | 2,722Kg |
| Power Req.: 230VAC, 230VAC, | 1 phase, 60 H 3 phase, 60 H | |



MD-AWD-500-XL

| Roll Diameter 12.625" 32.1cm Face Length 37" 93.9cm Inner Track 24" 60.9cm Outer Track 98" 248.9cr Wheelbase Range* 84-126" 213-32r Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | | | |
|---|------------------|-------------------|--|
| Roll Diameter 12.625" 32.1cm Face Length 37" 93.9cm Inner Track 24" 60.9cm Outer Track 98" 248.9cr Wheelbase Range* 84-126" 213-32r Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | Max Horsepower | , , , | |
| Face Length 37" 93.9cm Inner Track 24" 60.9cm Outer Track 98" 248.9cm Wheelbase Range* 84-126" 213-320 Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | Max Speed | 190MPH 306KPH | |
| Inner Track 24" 60.9cm Outer Track 98" 248.9cr Wheelbase Range* 84-126" 213-320 Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | Roll Diameter | 12.625" 32.1cm | |
| Outer Track 98" 248.9cr Wheelbase Range* 84-126" 213-32tr Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | Face Length | 37" 93.9cm | |
| Wheelbase Range* 84-126" 213-320 Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | nner Track | 24" 60.9cm | |
| Inertia 3,625 lbs(AWD) 2,000 lbs(2WD) | Outer Track | 98" 248.9cm | |
| 2,000 lbs(2WD) | Wheelbase Range* | 84-126" 213-320cr | |
| Max Axle Weight 6 000 lbs 2 722K | nertia | , , | |
| | Max Axle Weight | 6,000 lbs 2,722Kg | |
| Power Req.: 230VAC, 1 phase, 60 Hz, 40A - SI 230VAC, 3 phase, 60 Hz, 40A - DI | | | |

^{*} Longer wheelbase range available

Air Requirement for All AWD Dynamometers: 100-110 PSI, dry, regulated, oil-free.

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual Road Simulation Technology.



AWD Wheel Drive Dynamometers





AWD Wheel Drive Dynamometers







MD-AWD-800 Series

| Max Horsepower | 3,000HP(AWD) 2,000HP(2WD) | |
|------------------------------------|--------------------------------|-----------|
| Max Speed | 200MPH | 322KPH |
| Roll Diameter | 24" | 27.2cm |
| Face Length | 2x29" | 101.6cm |
| Inner Track | 28" | 71.1cm |
| Outer Track | 86" | 274.3cm |
| Wheelbase Range | 89-126" | 226-320cm |
| Inertia | 1,800 lbs(AWD) 900 lbs(2WD) | |
| Max Axle Weight | 10,000 lbs | 4,536Kg |
| Power Req.: 230VAC, 1 230VAC, 3 | phase, 60 Hz, phase, 60 Hz, | |

MD-AWD-1100 Series

| Max Horsepower | 3,500HP(AWD) 2,500HP(2WD) |
|------------------------------------|--|
| Max Speed | 225MPH 362KPH |
| Roll Diameter | 30" rear / 12.625" front |
| Face Length Rear | 37" front roll set 28/50" rear roll set |
| Inner Track | 30/24" (2WD/AWD) |
| Outer Track | 108/98" (2WD/AWD) |
| Wheelbase Range | 80-134" 203-340cm |
| Inertia | 3,300 lbs(AWD) 1,500 lbs(2WD) |
| Max Axle Weight | 10,000 lbs 4,536Kg |
| Power Req.: 230VAC, 1 230VAC, 3 | phase, 60 Hz, 40A - SE phase, 60 Hz, 40A - DE |

MD-AWD-1750 Series

| Max Horsepower | 3,500HP(AWD) 3,000HP(2WD) | |
|------------------------------------|-----------------------------------|--------------------|
| Max Speed | 250MPH | 402KPH |
| Roll Diameter | 50" rear / 12.625" front | |
| Face Length | 28" | 71.1cm |
| Inner Track | 30" | 76.2cm |
| Outer Track | 84" 96" option | 213.4cm 243.8cm |
| Wheelbase Range | 88-118" | 224-300cm |
| Inertia | 3,300 lbs(AWD) 2,5300 lbs(2WD) | |
| Max Axle Weight | 10,000 lbs | 4,536Kg |
| Power Req.: 230VAC, 1 230VAC, 3 | phase, 60 Hz phase, 60 Hz | • |

Air Requirement for All AWD Dynamometers: 100-110 PSI, dry, regulated, oil-free.

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual Road Simulation Technology.

Rollers: Knurled Finish, Bi-directional Roll Lock/Lift: Between roll lift with roll lock

MustangDyne.com



AWD Wheel Drive Dynamometers



MustangDyne.com 11 (330) 963-5400



EC997-13

Max Horsepower

Max Speed

Roll Width

Wheelbase

Inertia

Roll Diameter

Low Inertia Model

Cycles, Powersport Dynos



EC997 MC /QUAD-13 Low Inertia Model

| Max Horsepower | 750HP | |
|----------------|---------|---------|
| Max Speed | 200MPH | 322KPH |
| Roll Diameter | 12.625" | 32.1cm |
| Roll Width | 35" | 89.0cm |
| Wheelbase | 96" | 243.8cm |
| Inertia | 407 lbs | 185kg |

EC997-20 High Speed Model

| Max Horsepower | 1000HP | |
|----------------------------|---------|---------|
| Max Speed | 225MPH | 362KPH |
| Roll Diameter | 19.75" | 50.2cm |
| Roll Width | 12" | 30.5cm |
| Wheelbase | 96" | 243.8cm |
| Inertia | 233 lbs | 106kg |
| Longer Wheelbase Available | | |

750HP

200MPH

12 625"

174 lbs

12"

96"

322KPH

32 1cm

30 5cm

243.8cm

79kg

EC997-20 High Speed Model

| Max Horsepower | 1000HP | |
|----------------------------|---------|---------|
| Max Speed | 225MPH | 362KPH |
| Roll Diameter | 19.75" | 50.2cm |
| Roll Width | 19.88" | 50.5cm |
| Wheelbase | 96" | 243.8cm |
| Inertia | 500 lbs | 227kg |
| Longer Wheelbase Available | | |



MD-SXS/UTV

| Max Horsepower | 850HP | |
|------------------|---------|---------|
| Max Speed | 200MPH | 322KPH |
| Roll Diameter | 12.625" | 32.1cm |
| Inner Track | 19" | 48.3cm |
| Outer Track | 80" | 203.2cm |
| Inertia MC Mode | 394 lbs | 179kg |
| UTV/SxS/ATV mode | 671 lbs | 304kg |

Controls: Closed Loop Digital Controller with web based Hole Shot Software. Includes patented Virtual Road Simulation Technology.



Cycles, Powersport Dynos





Perfect for trade events, marketing campaigns, equipmentsharing arrangements, rental agreements, portable emissions testing... you name it!

Depending upon the dynamometer that is selected, Mustang can offer an enclosed trailer design or a flatbed trailer-mounted portability system to meet your specific application requirements.

Enclosed Trailer Design

A popular portable dyno setup is to incorporate a pallet jack and caster sets into the frame of the dyno, allowing it to be easily raised and pulled around the shop floor or moved from one location to another inside an enclosed trailer. An electric winch is often used to pull a portable dyno up a set of ramps and into an enclosed trailer

Flatbed Trailer Design

For larger systems, such as an AWD-500, the dynamometer is built directly into the chassis of a flatbed trailer. All components of the system are also cleverly designed into the flatbed trailer making setup of the system effortless. Simply park the trailer, lower the ramps, plug everything in, strap it down, and you are off and running in no time at all. A portable MD-AWD-500 is a true show-stopper. Add a drag racing tree and a few large screen monitors running Mustang's DragSim Drag Racing Simulator and you will draw a large crowd to watch real-world simulations of 1/4 mile and 1/8 mile drag racing. A trailer-mounted MD-AWD-500 is the ultimate promotional tool.



Heavy-Duty and Emissions Testing

Heavy Duty

Mustang designs and manufactures a line of heavy-duty dynamometers for testing of diesel, electric and hybrid electric vehicles such as trucks, buses and commercial vehicles in addition to the standard car or light duty pick-ups. Several of these products are certified in the states of Colorado, Nevada and Utah for use in loaded-mode diesel smog testing programs because of its accuracy and reliability. No other dyno in its class offers more value or better in-house motor vehicle testing capabilities than Mustang's line of Heavy-duty Chassis Dynamometers..

MD-250-HD

Max HP: 1,500hp Max Speed: 175mph

MD-1000

Max HP: 2,000hp Max Speed: 125mph

MD-7500-HD Max HP: 3,000hp Max Speed: 100mph

Emissions Dynamometers

Mustang Dynamometer has set the standards for equipment manufactured and used worldwide for centralized emissions

testing. Our pioneering experience has led us to be the world leader in the design and manufacturing of rugged inspection and maintenance hardware and software for the I/M industry. We have centralized testing lanes installed all over the world in climates from cold to hot and from wet to dry, all



designed to meet our customer's demands.

Visit MustangDyne.com for More Information

Or Contact Sales@MustangDyne.com for more details.





Accessories and Upgrades

Mustang Dynamometer has many essential accessories for any complete dyno cell, as well as promotional items as well. Visit MustangDyne.com for more details.



Jbax

As the primary vehicle data collection device, the Jbox is portable and connected by 15-ft USB cable to the server and has all the inputs ports for tachometer and all the sensors needed



Air/Fuel Ratio Oxygen Sensor

Accurately determine exhaust gas mixture over a wide range of engine conditions with this air/ fuel ratio oxygen sensors. Integrates controller/ data acquisition system for graphing AFR against horsepower, torque and engine RPM.



Jbox Accessory Kit

Measure engine speed by clamping the Inductive Pickup Sensor around a secondary ignition cable. While traditionally used on a Spark Plug wire, it can also be used on a coil wire for a better response.



OBD-II Adapter w/Software

Provides a direct connection to the vehicle's OBDII port, where every critical engine parameter can be captured directly from your vehicle's computer into the dynamometer controller software



Optical RPM Pickup Sensor

Unaffected by electromagnetic interference, this sensor works by monitoring light as it bounces off a piece of reflective tape applied to a rotating object.



Oil Temperature Sensor

Accurately measure and monitor engine oil temperature. Closely monitoring engine oil temperature ensures your dyno runs are comparable and increases repeatability.



Accessories and Upgrades



Aluminum Ramps

Manufactured from high strength aluminum material, Mustang's ramp package is lightweight and easy to move in and out of position by a single person.



Premium Engine Cooling Fan

Generates up to 32,000 CFM and features a variable speed motor controller to match the fan's output airflow to the dynamometer's roll speed.



Composite Ramps

Available for the MD-150 series chassis dynamometers, and manufactured from light weight industrial composite, these ramps are lightweight and easy to move in and out of position by a single person.



Premium Five Gas Analyzer

Accurately measure the 5 major gases contained in the vehicle exhaust stream. Seamlessly integrated with your dyno controls, DAC system for graphing each gas against horsepower, torque and engine RPM.



Standard Engine Cooling Fan

Generates air flow of 10,800 CFM. Additional options include automatic fan speed controller and adjustable fan height.



Exhaust Extractor Unit

This system is the best way to protect mechanics and garage employees from the potentially harmful gases released from vehicles running on the dyno is to capture it at the source: directly at the tailpipe.

Mustang Dynamometer has many essential accessories for any complete dyno cell, as well as promotional items as well. Visit MustangDyne.com for more details.




Controls Systems: Hole Shot™ Software

Hole Shot™ Control Software

Mustang adopted web-based technology in 2016 when it embarked on a new project to advance dynamometer technology and simplify its offerings. Mustang's goal was to increase commonality and provide customers with a more powerful and easier to manage controls package. Mustang already offered a full menu of testing capabilities. *Hole Shot* control software increases access and decreases clutter. Being a web-based systems, Mustang can better service thousands of customers world-wide from one location and keep them on the most up to date system available. All enhancements can be pushed to all customers at the same time making sure all installations are up to date.

Hole Shot control software comes standard with every new performance chassis dynamometer Mustang produces. The software offers an advanced DragSim feature that includes custom 3D drag strips, vehicle avatars, and playback modules that allows your customers to share their experience with others.



Customizable Interface



Wireless Access



Live Data Broadcast



Scheduling, Loading Data



MustangDyne.com



Controls Systems: Hole Shot™ Software



Benefits

- Automatic system upgrades via cloud computing
- Service and support the dynamometer via the web making resolving issues easier
- · Video streaming capabilities for viewing and interacting
- · Multiple clients can log into the system all at the same time
- Designed for Remote Teaching and Learning

Mustang Dynamometer's *Hole Shot* dynamometer controls software utilizes web based techniques, an HD camera, social media and modern tech to help transform your Mustang dyno into a self-promoting digital business. Customers can schedule runs, obtain their data and share results via an app we provide making data entry a thing of the past; simply enter in the user's handle or email address, click on their icon and start testing. Shop branded videos, runs and photos are automatically delivered to your customer from the software eliminating the need to print results.

Because of its capabilities, *Hole Shot* software is perfect for remote learning for automotive technical schools as well as performance tuning shops.

Features

Linux powered 4U industrial rack mount chassis with powerful micro PC

- Mustang's GEN4 DAC32 32 bit digital controller
- Remote camera kit auto run record with your watermark
- Wi-fi OBDII
- Powerful data graphing utilities
- · Multiple run graph overlay
- Full database facility for storage/retrieval of test info
- Export data to your favorite programs
- Customizable test reports with your company logo
- Easily export graphs as .jpg files



6.191

6.007№

1.057 FRE

0:04,079

Visit **MustangDyne.com** for more information about *Hole Shot* control software.






Training, Education and Research

Installation Assistance & Operator Training!

Mustang Dynamometer has a team of highly-skilled technicians on staff to assist you with your dyno installation. Once your dyno arrives at your facility, one of our highly trained experts will be on





site for a full two days to assist you every step of the way to ensure that your dyno is installed properly, is running flawlessly, and your staff is familiar with its operation. This service is available worldwide and is your assurance of a flawless and quick installation.

While on-site for installation assistance, a Mustang technician will train your entire staff on the proper use of the dynamometer hardware and software. Mustang factory technicians know the dyno systems inside and out, and will fully train your staff, performing hands-on training, including vehicle set-up and

restraint, Hole Shot Software instruction, proper testing methods, troubleshooting, sensor and data acquisition usage, and tips on getting the most from your dyno.

Research and Development

Mustang Dynamometer continues to allocate a substantial amount of capital into Research and Development. This has allowed Mustang to lead the pack in new innovations and introduce new products to the market place in a timely fashion.

In today's dynamic environment, technology continues to change and Mustang is at the forefront of developing new technology and integrating this new technology into the testing world. This significant Research and Development budget has allowed Mustang to experience growth through these improvements and the development of new products and services. Our Research and Development efforts have lead to improved productivity and with this improved productivity we have been able to pass along savings to our customers. We make all attempts to anticipate customer demands and invest heavily for innovative solutions which always keeps Mustang ahead of the curve.



Factory Tours and Marketing Support

Want to see how a dyno is made?

We're proud of what we do, so we love to show off. We're so convinced that when you see the quality of our products and the way they are made, with all-American ingenuity, you'll be impressed. So much so, that you'll probably want to buy a dyno. To cover your travel expenses, we'll give you \$1,000.00 off the cost of a new chassis dynamometer.

Tours are 3 hours long, and are booked on weekdays, either 9:00 am to 12:00 noon, or 2:00 pm to 5:00 pm. Saturday tours are by special requests only. Email sales@mustangdyne.com for further details. For available/open dates, visit our website and fill out the request form.

- Quick visit with sales, operations, engineering and design departments
- Tour of Mustang's 100,000 square feet of manufacturing floor space
- See complete engineering, balancing, metal fabricating, machining, painting, assembly and testing operations
- · Witness a dyno pull of a company car
- Watch a demonstration of controls software.

Marketing Support

marketing support of Mustang Dynamometer behind them. banners, promotional From items, and social media "shout outs", Mustang helps each of their customers. Development Department. When a new dyno is shipped to a customer, that location is added to the dynolocator map on the Mustang website, which is a great marketing tool. This map is

Every customer who purchases a Mustang dyno has all the



the third most visited page on Mustang's website, and key in getting potential customers to find your location. If you are a new

customer to the Mustang family, interested in purchasing a dyno and have questions, feel free to contact Mustang Dynamometer.





Customers Testimonials

GIAC

"Tuning is an art. To tune for optimal performance is to tune for a careful combination of speed, strength and agility that varies as driver tastes vary. GIAC exists to tune cars for the way people like to drive. The MD-AWD-500 may be the finest tuning dynamometer on the market today, with the ability to plot power as load is applied to the wheels."

Garrett Lim, President
Garrett Integrated Automotive Corp. (GIAC)

JP Euro

In Garland Texas, JP Euro recently purchased a movable base, below-ground, MD-AWD-800-BG dyno and has this to say about it: "Big shout out to team Mustang dyno! These guys are second to none! Don, Mike and the entire crew. If you are in doubt (about) writing a 100K check. DON'T. Mustang Dyno buy Once.. Cry Once!!!!!""

McClaren Phan Owner JP Euro



S3 Stout Speed Solutions

"We love our Mustang MD-1100-SE dyno. We use it often, and it has helped us with promoting our place. It's reliable, consistent, and has been a great asset. It's been an investment worth having. It's been a selling feature for our shop. And the Hole Shot software is easy to set the load, run quarter mile drag tests. And we keep a score of who holds the highest horsepower on record for our dyno. The customer service has been great. If there's any problems, we give Mustang a call and we figure it out and get it running as good as new. I can't say enough how tremendous it has been to own a Mustang dyno."

Brian Stout, Senior Stout Speed Solution





Customers Testimonials

Area1320

"We have had our Mustang Dynamometer for 6+years. In that time we have racked up almost 55,000 miles on it. Let's just say we use it a lot. We may not post every car on the dyno but we sure use the hell out of it. And its treated us great because we maintain it religiously. Great product, great people, great company to deal with."

Area1320 Nazareth, PA Area1320.com



Buschur Racing, Inc.

"I've been in business for 19 years racing and tuning turbocharged 4 cylinders. In this time we've attempted to tune on other dyno's and even owned another brand. After learning that our time spent on these other dynos was worthless when we'd get to the track we decided to try the Mustang Dyno. After a lot of looking around we decided on the MD AWD 500SE dyno. I've never looked back since. It has been dead reliable for the last 3 years with not a single problem. We now tune every single car we build on the dyno and find no need for street tuning. When the cars hit the race track they are tuned correctly. Instead of spending time doing further tuning like we had to do in the past, now we can just concentrate on setting more records "

David Buschur President Buschur Racing, Inc.

AEM

"We use our dyno daily and it has performed very well and has been very reliable. Most importantly, we have found that Mustang has been an excellent partner with respect to helping us with the servicing of the dynamometer. The customer service group has been VERY responsive and helpful whenever we have needed help. With the shift in the market to more R&D of performance EVs, which output big torque at low RPM, we had Mustang upgraded our MD-1750 dyno with a second power absorber unit (PAU) and both new hardware and software to the controls system. Now our dyno can handle max speed of 250 mph, and a HP measurement rating of 3,500-hp."

John P. Concialdi AEM











Mustang Dynamometer

2300 Pinnacle Parkway Twinsburg, OH 44087 Phone: (330) 963-5400 Fax: (330) 425-3310

Email: Sales@MustangDyne.com

MustangDyne.com

Mustang Dynamometer Core Values

For over 50 years, Mustang Dynamometers has been a leading manufacturer and designer of the highest quality, most accurate chassis dynamometers for the performance market and emission testing programs worldwide. Our sister company, Mustang Advanced Engineering, has created world leading testing solutions for advanced hybrid and electric vehicle development, wind turbine gearbox testing, military vehicle development test stands and advanced testing and simulation systems for tomorrow's future technologies. Visit MustangDyne.com or more information. Follow them on Facebook, Twitter, LinkedIn, and Instagram.



Photography courtesy of Mid Florida Dyno, Area1320, JP Euro, Renn Sport Performance - RSP, S3 Stout Speed Solution, EnginePlus Motorsports, Speed Society, Garrett Tuning, and RE Performance & Tuning

© 2025 Mustang Dynamometer Mustang Dynamometer, PowerDyne and Hole Shot are trademarks or registered trademarks of Mustang Dynamometer